

CETO

WALL LIGHT - OFFSET

Ceto captures the variation and rippling of the surface of the ocean. Each piece reflects a unique pattern, emitting a delicate luminosity, highlighting the presence of the sea. This sculptural luminaire is available in a selection of mouth-blown glass finishes combined with a highly refined machined aluminium body available in a black and champagne anodised finish. The Ceto Wall Light reflects the shadows of the glass against the wall, replicating the natural flow and movement of water.

AVAILABLE FINISHES













TECHNICAL

MATERIAL ANODISED ALUMINIUM, GLASS

SELV 60V (WITH EXTERNAL DRIVER) LAMPING CWL1 - 3.7W, 400LM, 3000K

CWL2 - 5.6W, 800 LM, 3000K

DIMMING 220-240V REGION

OPTIONS PHASE - DIMMING RANGE 5 - 100% - DIMMING RANGE 1 - 100%

DALI

110-120V REGION

PHASE - DIMMING RANGE 3 - 100% - DIMMING RANGE 0.1 - 100% DALI

ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS.

FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING

RANGE OF THE FIXTURE.

DRIVER SIZE

220 -240V PHASE / TRIAC

CWL1 & CWL2 - L101 X W51 X H29 / L4" X W2" X H1.1"

CWL1 & CWL2 - L120 X W51 X H29 / L4.7" X W2"/ X H1.1"

PHASE / TRIAC 110-120V

CWL1 & CWL2 - L75 X W35 X H26.5 / L3" X W1.4" X H1"

CWL1 & CWL2 - L75 X W35 X H26.5 / L3" X W1.4" X H1"

MOUNTING WALL MOUNT BODY Ø100MM / 3.9".

FOR PROPER COVERAGE OF 4" JUNCTION BOXES, A Ø120MM / 4.7" COVER PLATE IS PROVIDED FOR US/CAN ORDERS.

LED LIFESPAN 50,000 HRS

CERTIFICATION AU/N7 AS/NZS 60598.1, 60598.2.1

EN 60598.1, 60598.2.1 ETL/UL1598, CSA C22.2#250.0

IP RATING IP20 - FOR INDOOR USE ONLY

SKU CODES EG. CWL1.G-BLK.A-BLK =

CETO WALL LIGHT WITH OFFSET MOUNT IN BLACK GLASS

WITH A BLACK ANODISED FRAME

CWL1.G-XXX.A-XXX CETO SINGLE WALL LIGHT WITH OFFSET MOUNT

CETO DOUBLE WALL LIGHT

CWL2.G-XXX.A-XXX WITH OFFSET MOUNT

FINISHES GLASS

DIMENSIONS

FROSTED BLACK (G-FBK) BLACK (G-BLK)

CLEAR (G-CLR) WHITE (G-WHT)

BODY BLACK ANODISED (A-BLK)

CHAMPAGNE ANODISED (A-CHM)

VARIOUS - SEE DIMENSIONS ON FOLLOWING PAGE*

PRODUCT CWL1 - 2KG / 4.4LB CWL2 - 4KG / 9LB WEIGHT

PACKAGING CWL1 - L 580 W 350H 250 / L 20" W 20" H 9.8" DIMENSIONS CWL2 - L 500 W 500 H 250 / L 20" W 20" H 9.8"

PACKAGING CWL1 - 2KG / 4.4LB CWL2 - 4KG / 9LB WEIGHT

twentieth

DIMENSIONS



W 200 H 400 D 107 W 7.9" H 15.8" D 4.2"



W 200 H 650 D 107 W 7.9" H 25.6" D 4.2"

