

NEBULAE

WALL LIGHT

The Nebulae collection takes its name from the natural phenomena of interstellar clouds and their dynamic layered lighting effects. The geometric machined forms coupled with the fluid glass discs creates a balance between the elements. The Nebulae Wall Light is a statement in any space and supplies a beautiful adjustable light level. The wall light can be specified with a single glass disc or layered with an additional disc to create expansive light dispersion options. The body is manufactured from machined aluminium champagne or black anodised. Nebulae's discs come in a fluted clear, bubbled black, rippled blue or white pearl glass, in singular or doubled.

AVAILABLE FINISHES













TECHNICAL

MATERIAL ANODISED ALUMINIUM, GLASS SKU CODES EG. NW.G-FLU.A-WCH = NEBULAE WALL LIGHT IN FLUTED

CLEAR GLASS WITH CHAMPAGNE ANODISED CANOPY AND LAMPING 240V - 10W LED, 990LM, 3000K, WARM WHITE, DIMMABLE CENTRAL PIN

FINISH

120V - 13W LED, 1190LM, 2900K, WARM WHITE, DIMMABLE

NW.G-XXX.A-XXX NEBULAE WALL LIGHT LED LIFESPAN 15,000 HRS

CONTROL PHASE (TRAILING EDGE/LEADING EDGE) - DIMMING RANGE GLASS FLUTED CLEAR (G- FLU) 5 - 100%, DIGITAL / SMART SYSTEMS (DALI/CBUS) - NON-BUBBLE BLACK (G-BBL)

DIMMABLE, ON/OFF FUNCTIONALITY ONLY VIA DALI SWITCH WHITE PEARL (G-PWH) (SWITCH NOT SUPPLIED). 1-10V / 0-10V - NOT COMPATIBLE RIPPLED BLUE (G-RPL)

**FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND BLACK ANODISED (A-BLK) CANOPY SOURCING A ROTARY OR PUSH BUTTON DIMMER WITH CHAMPAGNE ANODISED (A-CHM) ADJUSTMENT DIAL CAPABLE OF SETTING THE DIMMING

RANGE OF THE FIXTURE. DIMENSIONS Ø300 D 56 / Ø11.8" D 2.2"

IP RATING IP20 - FOR INDOOR USE ONLY WEIGHT 1.5KG / 3.3LB

CERTIFICATION AU/NZ AS/NZS 60598.1, 60598.2.1 PACKAGING

EN 60598.1, 60598.2.1 DIMENSIONS L 350 W 350 H 70 / L 13.8" W 13.8" H 2.8" US/CAN ETL/UL 1598, CSA C22.2#250.0

WEIGHT

PACKAGING 2KG / 4.4LB

DIMENSIONS





NW Ø300 D56 CANOPY Ø130 Ø11.8" D2.2" CANOPY Ø5.1"

