

VOLANT

WALL LIGHT


Volant features solid brass bars, paired with textured, tubular formed-glass elements, creating a statement luminaire. This delicate light creates an equilibrium between the different materials and offers a beautifully soft level of luminosity.

Volant's architectural nature allow the fixture to span across a plethora of interior spaces. The solid brass bars are individually machined with the luminaire defined by a white glass diffuser which is pinned in-place to the solid brass bar. Textured tubular glass elements are balanced on the same pins creating a uniquely formed illumination.

AVAILABLE FINISHES



DIMENSIONS





VW1 W 70 H 500 D 80 W 2.8" H 19.7" D 3.2"

VW2 W 160 H 500 D 80 W 6.3" H 19.7" D 3.2"

*DOTTED LINE REPRESENTS OPTIONAL JUNCTION BOX COVER PLATE

TECHNICAL

MATERIAL	TREATED BRASS, GLASS		CERTIFICATION	AU/NZ EU		60598.1, 60598.2.1 8.1, 60598.2.1	
FINISH	ALL BRASS FRAMES ARE BRUSHED AND TREATED TO			US/CAN		ERTIFICATION PENDING	
FINISH		AVAILABLE FINISH OPTIONS, THEN SEALED		00/0AN	LIL/OLC		
	TO PREVENT ACCELERATED AGING.		WALL MOUNT	VW1 - H 330 X W 22 / H 13" X W 0.9" VW2 - H 330 X W 15.5 / H 13" X W 0.6"			
			DIMENSIONS				
LAMPING	SELV 60V (EXTERNAL DRIVER SUPPLIED)		BIIIIEIIOIOIIO	1112 110000			
	VW1 - 5.3W, 766 LM, 2700K			TO ENSURE CORRECT COVERAGE OVER 4" JUNCTION BOXES AN ADDITIONAL MOUNTING PLATE (Ø110MM / 4.3") & COVER PLATE (250MMH X 120MMW / 9.9"H X 4.7"W) IS SUPPLIED FOR US/CAN REGIONS. MOUNTING HOLES			
	VW2 - 7.8W, 1186 LM, 2700K						
DIMMING	220-240V REGION						
OPTIONS	PHASE	- DIMMING RANGE 5 - 100%		DESIGNED TO SUIT STANDARD 4" OCTAGONAL JUNCTION BOXES. MOUNT & COVER PLATES ARE NOT SUPPLIED FOR OTHER REGIONS.			
	DALI	- DIMMING RANGE 1 - 100%					
	110-120V REGIO						
	PHASE	- DIMMING RANGE 3 - 100%	SKU CODES	KU CODES EG. VW2.G-FLU.BR-BRZ VOLANT DOUBLE WALL LIGHT IN FLUTED CLEAR GLASS WITH A BRONZED BRASS FRAME			
	DALI	- DIMMING RANGE 0.1 - 100%					
			WITH A BROD	NZED BRASS	FRAME		
	ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS.			VW1.G-XXX.B		VOLANT SINGLE WALL LIGHT	
	COMPONENTH	CENTIFIED FOR USE IN THESE REGIONS.		VW1.G-XXX.E		VOLANT DOUBLE WALL LIGHT	
	FOR OPTIMAL	DIMMING PERFORMANCE WE RECOMMEND					
	SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.		FINISHES				
			GLASS	FROSTED BLACK (G-FBL)			
				FLUTED (G-F			
DRIVER SIZE				FROSTED FL	UTED (G-FFL)	
220 -240V	PHASE/TRIAC						
	ALLVW	- L101 X W51 X H29 / L4" X W2" X H1.1"	FRAME	BRUSHED BRASS (BR-NAT) BLACKENED BRASS (BR-BLK)			
	DALI			BRONZED BF	IASS (BH-BH2	2)	
	ALLVW	- L120 X W51 X H29 / L4.7" X W2" X H1.1"	PRODUCT	1000			
110-120V			PRODUCT	VW1	2KG / 4.4		
110-1207	PHASE / TRIAC	- L75 X W35 X H26.5 / L3" X W1.4" X H1"	WEIGHT	VW2	5KG / 11L	В	
	ALL VVV	- E/5 X W35 X H20.57 E5 X W1.4 X H1	PACKAGING	VW1	1 X 2KC /	C CL D	
	DALI		WEIGHT	VW2	1 X 3KG / 6.6LB 1 X 6KG / 13.2LB		
	ALLVW	- L88 X W43 X H26.5 / L3.5" X W1.7" X H1"	WEIGHT	V VVZ	1X ONG /	13.2LD	
	ALL V W - LOO A W43 A HZU.57 LS.5 A W1.7 A HI		PACKAGING	VW1 L 550 W 260 H 100 / L 21.6" W 10.3" H 4"			
LED LIFESPAN	ESPAN 50,000 HRS		SIZE	VW2 L 550 W 340 H 100 / L 21.6" W 10.3" H 4"			
220 En EOM	30,000 1110		0.22	1112	2000 111		
IP RATING	IP20 - FOR INDOOR USE ONLY						



sales@twentieth.net 323.904.1200 www.twentieth.gallery

twentieth sales@twentieth.net 323.904.1200 www.twentieth.gallery

