



CETO


WALL LIGHT - OFFSET

Ceto captures the variation and rippling of the surface of the ocean. Each piece reflects a unique pattern, emitting a delicate luminosity, highlighting the presence of the sea. This sculptural luminaire is available in a selection of mouth-blown glass finishes combined with a highly refined machined aluminium body available in a black and champagne anodised finish. The Ceto Wall Light reflects the shadows of the glass against the wall, replicating the natural flow and movement of water.

AVAILABLE FINISHES



DIMENSIONS



CWL1
W 200 H 400 D 107
W 7.9" H 15.8" D 4.2"

*DOTTED LINE REPRESENTS
OPTIONAL US/CAN JUNCTION
BOX COVER PLATE



CWL2
W 200 H 650 D 107
W 7.9" H 25.6" D 4.2"

*DOTTED LINE REPRESENTS
OPTIONAL US/CAN JUNCTION
BOX COVER PLATE

TECHNICAL

MATERIAL	ANODISED ALUMINIUM, GLASS		MOUNTING	WALL MOUNT BODY Ø100MM / 3.9".	
LAMPING	FIXED TEMP - 2700K SELV 60V (WITH EXTERNAL DRIVER) CWL1 - 3.7W CWL2 - 5.6W			US / CAN MOUNTING OPTION 1 – JUNCTION BOX COVER PLATE FITS STANDARD 4" OCTAGONAL JUNCTION BOXES. INCLUDES COVER PLATE (Ø4.7") AND A MOUNTING PLATE.	
	DIM TO WARM - 1800-3000K SELV 60V (WITH EXTERNAL DRIVER) CWL1 - 4.7W CWL2 - 8.2W			OPTION 2 – JUNCTION BOX RENDER PLATE RENDER PLATE MOUNTED DIRECTLY TO JUNCTION BOX AND PATCHED AND PAINTED OVER.	
	LUMEN OUTPUT BASED ON FINISH CLEAR - 440LM WHITE - 430LM BLACK - 230LM FROSTED BLACK - 130LM			EITHER OPTION SUPPLIED ONLY FOR US/CANADA ONLY. CONTACT STUDIO FOR FURTHER DETAILS.	
DIMMING OPTIONS	220-240V REGION PHASE DIMMING RANGE 5 - 100% DALI DIMMING RANGE 1 - 100%		SKU CODES	EG. CWL1.G-BLK.A-BLK = CETO WALL LIGHT WITH OFFSET MOUNT IN BLACK GLASS WITH A BLACK ANODISED FRAME	
	110-120V REGION PHASE DIMMING RANGE 3 - 100% DALI DIMMING RANGE 0.1 - 100%			CWL1.G-XXX.A-XXX CETO SINGLE WALL LIGHT WITH OFFSET MOUNT	
				CWL2.G-XXX.A-XXX CETO DOUBLE WALL LIGHT WITH OFFSET MOUNT	
	ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS.			FINISHES GLASS	
DRIVER SIZE 220 -240V	FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.		BODY	FROSTED BLACK (G-FBK) BLACK (G-BLK) CLEAR (G-CLR) WHITE (G-WHT)	
110-120V	PHASE - L101 X W51 X H29 / L4" X W2" X H1.1" DALI - L144 X W30 X H21 / L5.7" X W1.2" / X H0.8"		DIMENSIONS	VARIOUS - SEE DIMENSIONS ON FOLLOWING PAGE*	
LED LIFESPAN	PHASE - L75 X W35 X H26.5 / L3" X W1.4" X H1" DALI - L75 X W35 X H26.5 / L3" X W1.4" X H1"		PRODUCT WEIGHT	CWL1 - 2KG / 4.4LB CWL2 - 4KG / 9LB	
IP RATING	50,000 HRS		PACKAGING DIMENSIONS	CWL1 - L 580 W 350H 250 / L 20" W 20" H 9.8" CWL2 - L 500 W 500 H 250 / L 20" W 20" H 9.8"	
CERTIFICATION	IP20 - FOR INDOOR USE ONLY		PACKAGING WEIGHT	CWL1 - 2KG / 4.4LB CWL2 - 4KG / 9LB	
CERTIFICATION	AU/NZ	AS/NZS 60598.1, 60598.2.1			
	EU	EN 60598.1, 60598.2.1			
	US/CAN	ETL/UL 1598, CSA C22.2#250.0			