



CETO

LINEAR WALL LIGHT

Ceto captures the variation and rippling of the surface of the ocean. Each piece reflects a unique pattern, emitting a delicate luminosity, highlighting the presence of the sea. The Ceto Linear Wall light is available in a selection of mouth-blown glass finishes combined with a highly refined machined aluminium body available in a black and champagne anodised finish. Each glass piece is designed to rotate around the central stem, reflecting the shadows of the glass against the wall, replicating the natural flow and movement of water.


AVAILABLE FINISHES



TECHNICAL

MATERIAL	ANODISED ALUMINIUM, GLASS	IP RATING	IP20 - FOR INDOOR USE ONLY
LAMPING	FIXED TEMP - 2700K 8.1W, SELV 60V (WITH EXTERNAL DRIVER) DIM TO WARM - 1800-3000K 10W, SELV 60V (WITH EXTERNAL DRIVER) LUMEN OUTPUT PER SHADE CLEAR - 440LM WHITE - 430LM BLACK - 230LM FROSTED BLACK - 130LM	MOUNTING	WALL MOUNT BODY Ø44.5MM / 1.75". US / CAN MOUNTING OPTION 1 – JUNCTION BOX COVER PLATE FITS STANDARD 4" OCTAGONAL JUNCTION BOXES. INCLUDES COVER PLATE (Ø4.7") AND A MOUNTING PLATE. OPTION 2 – JUNCTION BOX RENDER PLATE RENDER PLATE MOUNTED DIRECTLY TO JUNCTION BOX AND PATCHED AND PAINTED OVER.
DIMMING OPTIONS	220-240V REGION PHASE DIMMING RANGE 5 - 100% DALI DIMMING RANGE 1 - 100% 110-120V REGION PHASE DIMMING RANGE 3 - 100% DALI DIMMING RANGE 0.1 - 100% ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS. FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.	SKU CODES	EG. CWL3.G-BLK.A-BLK = CETO LINEAR WALL LIGHT WITH OFFSET MOUNT IN BLACK GLASS WITH A BLACK ANODISED FRAME CWL3.G-XXX.A-XXX CETO LINEAR WALL LIGHT WITH OFFSET MOUNT FINISHES GLASS FROSTED BLACK (G-FBK) BLACK (G-BLK) CLEAR (G-CLR) WHITE (G-WHT) BODY BLACK ANODISED (A-BLK) / CHAMPAGNE ANODISED (A-CHM)
DRIVER SIZE 220 -240V	PHASE - L101 X W51 X H29 / L4" X W2" X H1.1" DALI - L144 X W30 X H21 / L5.7" X W1.2" / X H0.8"	DIMENSIONS	W 200 H 1010 D 140 / W 7.9" H 40" D 5.5"
110-120V	PHASE - L75 X W35 X H26.5 / L3" X W1.4" X H1" DALI - L75 X W35 X H26.5 / L3" X W1.4" X H1"	PRODUCT WEIGHT	CWL3 - 7KG / 15.4LB
CERTIFICATION	AU/NZ AS/NZS 60598.1, 60598.2.1 EU EN 60598.1, 60598.2.1 US/CAN ETL/UL 1598, CSA C22.2#250.0	PACKAGING DIMENSIONS	CWL3 - L 750 W 500 H 250 / L 30" W 20" H 9.8"
LED LIFESPAN	50,000 HRS	PACKAGING WEIGHT	CWL3 - 7KG / 15.4LB

DIMENSIONS



CWL3
W 200 H 1010 D 140
W 7.9" H 40" D 5.5"
WALL CANOPY SPACING 340MM / 13.39"

*DOTTED LINE REPRESENTS
OPTIONAL US/CAN JUNCTION
BOX COVER PLATE