


Roll & Hill

CONTENTS

Pith Sconce (120V/240V)




(x2) 8-32 J box Screw




(x7) Wago Connectors



Driver




(x4) Toggle anchor
(240V only)



(x4) Metal screw
(240V only)




(x4) Wood screw
(240V only)



(x4) Long 8-32 screw
(240V only)



Driver Box
(240V only)



SAFETY INFORMATION

UL/Outdoor wet rated.

Maximum ambient temperature: 25°C


The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.

Roll & Hill

PITH SCONCE (120V) | INSTALLATION

Note: Please contact a licensed electrician.

01. Unscrew the thumb nut (A) to release the round plate (B), the washer (C), check plate (D), diffuser (E), and the crossbar with LED assembly (F).




Roll & Hill


PITH SCONCE (120V) | INSTALLATION

Note: Please contact a licensed electrician.

02. Take the LED driver (G), and connect the lead wires with the provided 2-port wago (H) from the J-box (I).
03. Fit the LED driver inside the J-box and tuck in the lead wires.



04. Bring the crossbar with LED assembly (F) up to the J-box (I), and make the ground wire connection using the provided 2-port wago (J).
05. Then make the low voltage wire connection with the provided 2-port wago (K).




Roll & Hill


PITH SCONCE (120V) | INSTALLATION

Note: Please contact a licensed electrician.

06. Tuck all the wires into the J-box (I), and secure the crossbar assembly (F) with two provided 8-32 screws (L).



07. Reassemble the parts to complete the fixture, by fitting the round plate (B) onto the thumb nut (A), then the washer (C), and check plate (D).
08. Then hold the diffuser (E) up to the crossbar assembly (F), and screw in the thumb nut (A) with all the parts (B,C, and D) into the crossbar assembly.




Roll & Hill

PITH SCONCE (240V) | INSTALLATION

Note: Please contact a licensed electrician.

01. Unscrew the thumb nut (A) to release the round plate (B), the washer (C), check plate (D), diffuser (E), and the crossbar with LED assembly and 240V driver enclosure (F).




Roll & Hill

PITH SCONCE (240V) | INSTALLATION

Note: Please contact a licensed electrician.

02. Connect the lead wires (E) to the power supply wires.

03. Mount the crossbar to the wall using the provided screws (H).



Roll & Hill

PITH SCONCE (240V) | INSTALLATION

Note: Please contact a licensed electrician.

07. Reassemble the parts to complete the fixture, by fitting the round plate (B) onto the thumb nut (A), then the washer (C), and check plate (D).
08. Then hold the diffuser (E) up to the crossbar assembly (F), and screw in the thumb nut (A) with all the parts (B,C, and D) into the crossbar assembly.

